

QUINTIN CERTIFICATIONS
1031 route de Saint Ange
38760 VARGES ALLIERES
ET RISSET - France
Tél. +33.(0)7 66 29 39 28
g.quintin.consult@gmail.com
www.quintincertifications.com

CERTIFICATE OF CONFORMITY N°RQC2020-025/A

1. APPLICANT

Applicant: Mr Yvan BURON
Manufacturer : SARL VERTVOLTIGE INNOVATION – 2 rue du Parc National - 64260 ARUDY - France

2. EQUIPMENT

Type of equipment : **Anchor device type C – EN 795 : 2012* and TS 16415 :2013***
Trademark : **VERTICAL TREK INNOVATION**
Reference : **Ligne de vie horizontale X-TREK**

3. DESCRIPTION

Main characteristics	Componants	References
<ul style="list-style-type: none"> • Use in wall/floor position only, use in overhead position not allowed • Use in single or multispan • Span : minimum 3 m maximum 15 m • Number of users : 3 people • Use with mobile anchor OCHO PRO or connector EN 362 • Entry exit part : T-matrix or RUPT • No non-metallic element without proof of durability • Cable fixed in the anchors • Use with EN 360 and EN353-2: no system tested with the equipment • Maximum angle allowed: 15° 	<ul style="list-style-type: none"> • Stainless steel wire rope 7x19 ø 10 mm • Energy absorber anchor in stainless steel and aluminum • Entry exit part in stainless steel and aluminum • Entry exit part in stainless steel and aluminum • bifurcation cross in stainless steel • Post in stainless steel height 150 or 300 mm • Post in stainless steel height 150 or 300 mm • Post in stainless steel and aluminum • Extremity anchor in stainless steel + quick link 10 mm • Mobile anchor in stainless steel and aluminum 	<ul style="list-style-type: none"> • Cable • Pack Matrix • Pack T-matrix • RUPT • X-matrix • P.fix150 ou P.fix300 • P.twist150 ou P.twist300 • Cube • A-FIX • OCHO PRO

(full description and results in the conformity report n°RQC2020-025-1).

4. TECHNICAL REFERENTIAL

The anchor device type C has been evaluated according to the relevant requirement of the standard EN 795 : 2012* "Personal fall protection equipment – Anchor devices" and the technical specification TS 16415 :2013* "Personal fall protection equipment – Anchor devices – Recommendations for anchor devices for use by more than one person simultaneously".

5. CONDITION OF USE

This anchor device type C is not considered as personal protective equipment against falls from a height. It is intended to be used, in combination with other components, as personal protective equipment against falls from a height.

6. CONCLUSION

The Anchor device Type C, reference **Ligne de vie horizontale X-TREK**, presented by **VERTICAL TREK INNOVATION** and described in the conformity report RQC2020-025-1, conforms to the requirements of European standard EN 795:2012* and Technical Specification TS 16415:2013*.

27/08/2020
The head of QUINTIN CERTIFICATIONS
Guillaume QUINTIN



QUINTIN
Validation électronique

*Only the tests that fall within the COFRAC accreditation scope are marked with *. QUINTIN CERTIFICATIONS does not allow partial reproduction of this document and reproduction of the Cofrac logo. The full reproduction of this document is the only one allowed.*

Cette attestation d'une page ne constitue pas le justificatif prévu par le code de la consommation (article L-115-27) par lequel un organisme distinct du fabricant atteste à des fins commerciales qu'un produit est conforme à des caractéristiques dans un référentiel déposé auprès de l'autorité administrative

QUINTIN CERTIFICATIONS – 1031 route de Saint Ange – 38760 VARGES ALLIERES ET RISSET – France TEL +33 (0) 7 66 29 39 28 – Email : g.quintin.consult@gmail.com
SARL au capital de 10 000 € - SREN 848 919 676 - TVA intracommunautaire FR81848 919 676

QC-151-V1- Attestation de conformité Cofrac GB/RQC2020-025 A _VERTVOLTIGE INNOVATION GB/ 27/08/2020 09:06